

Application No.: «AppNumber»

Case No.: «CaseNumber»

Amendments to the Claims:

The following Listing of Claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (Currently Amended) A portable RFID reader for use in interrogating RFID tags associated with items of interest, comprising:

- (a) an RFID interrogation source;
- (b) an antenna;
- (c) a processor;
- (d) a display; and

(e) a user interface in which a representation of an interrogation area is shown on the display as a first graphical component of the user interface, and an item of interest is shown on the display as a second graphical component of the user interface relative to the first graphical component to indicate a location within the interrogation area in which at least one graphic associated with the item of interest may be presented on the display for observation by a user, wherein the RFID interrogation source is coupled to the processor, the antenna is coupled to either the RFID interrogation source or the processor, and the processor is coupled to the display.

2. (Canceled) The portable RFID reader of claim 1, wherein the graphic is representative of the item of interest.

3. (Canceled) The portable RFID reader of claim 1, wherein the graphic is representative of an area interrogated by the RFID reader.

4. (Original) The portable RFID reader of claim 1, wherein the processor and display are components of a hand-held computer.

5. (Original) The portable RFID reader of claim 1, wherein the display may be activated by touch.

Application No.: «AppNumber»

Case No.: «CaseNumber»

6. (Original) The portable RFID reader of claim 1, wherein the user interface further includes text associated with the item of interest may be presented on the display for observation by a user.

7. (Original) The portable RFID reader of claim 1, wherein the user interface further includes at least one audio signal for providing information to the user.

8. (Original) The portable RFID reader of claim 7, wherein the audio signal is provided each time an RFID tag is interrogated.

9. (Original) The portable RFID reader of claim 7, wherein the audio signal is only provided when the RFID tag of an item meeting a predetermined criterion is interrogated.

10. (Original) The portable RFID reader of claim 9, wherein the predetermined criterion is selected from a group consisting of:

- (a) a specific RFID tag associated with an item of interest;
- (b) an RFID tag that is out of order relative to the RFID tag of at least one adjacent item; and
- (c) a class of items to which the item of interest belongs.

11. (Original) The portable RFID reader of claim 10, wherein the criterion in response to which the audio signal is provided may be presented on the display for observation by a user.

12. (Original) The portable RFID reader of claim 1, wherein the user interface further includes at least one light for providing information to the user.

13. (Original) The portable RFID reader of claim 12, wherein at least one light is illuminated each time an RFID tag is interrogated.

Application No.: «AppNumber»

Case No.: «CaseNumber»

14. (Original) The portable RFID reader of claim 12, wherein the light is only illuminated when the RFID tag of an item meeting a predetermined criterion is interrogated.

15. (Original) The portable RFID reader of claim 14, wherein the predetermined criterion is selected from a group consisting of:

- 21
- (a) a specific RFID tag associated with an item of interest;
 - (b) an RFID tag that is out of order relative to the RFID tag of at least one adjacent item; and
 - (c) a class of items to which the item of interest belongs.

16. (Original) The portable RFID reader of claim 15, wherein the criterion in response to which the at least one light is illuminated may be presented on the display for observation by a user.

identical claims (1)
(17) (Currently Amended) A portable RFID reader for use in interrogating RFID tags associated with items of interest, comprising:

- (a) an RFID interrogation source;
- (b) an antenna;
- (c) a processor;
- (d) a display; and
- (e) a user interface in which a representation of an interrogation area is shown on the display as a first graphical component of the user interface, and an item of interest is shown on the display as a second graphical component of the user interface relative to the first graphical component to indicate a location within the interrogation area, wherein the RFID interrogation source is coupled to the processor, the antenna is coupled to either the RFID interrogation source or the processor, and the processor is coupled to the display.

18. (Original) The portable RFID reader of claim 17, wherein the first graphical component is a bar, and the second graphical component is a portion of the bar.

Application No.: «AppNumber»

Case No.: «CaseNumber»

19. (Original) The portable RFID reader of claim 17, wherein the first graphical component is a group of icons, and the second graphical component is one of the icons of the series, in which the one icon is visually differentiated from the remainder of the icons.

20-21. (Cancelled)

22. (Currently Amended) An RFID reader comprising:

- B1
- (a) an RFID interrogation source;
 - (b) a processor;
 - (c) a display; and
 - (d) a user interface in which a representation of an interrogation area is shown

on the display as a first graphical component of the user interface, and an item of interest is shown on the display as a second graphical component of the user interface relative to the first graphical component to indicate a location within the interrogation area and which an audio signal is produced when the RFID reader interrogates an RFID tag associated with a predetermined location, wherein the RFID interrogation source is coupled to the processor and the processor is coupled to the display.

23. (Currently Amended) An RFID reader comprising:

- (a) an RFID interrogation source;
- (b) a processor;
- (c) a display; and
- (d) a user interface in which an audio signal is produced repeatedly at a

desired interval to pace a user as to the speed at which RFID tags should be interrogated, wherein the RFID interrogation source is coupled to the processor and the processor is coupled to the display.

24. (Currently Amended) An RFID reader comprising:

- (a) an RFID interrogation source;
- (b) a processor;

Application No. «AppNumber»

Case No.: «CaseNumber»

(c) a display; and

(d) a user interface in which a representation of an interrogation area is shown on the display as a first graphical component of the user interface, and an item of interest is shown on the display as a second graphical component of the user interface relative to the first graphical component to indicate a location within the interrogation area and including at least one light that is illuminated when an RFID tag is interrogated, wherein the RFID interrogation source is coupled to the processor and the processor is coupled to the display.

25. (Original) The RFID reader of claim 24, wherein the light is illuminated only when an RFID tag associated with a specific material of interest is interrogated.

26. (Original) The RFID reader of claim 24, wherein at least one light remains illuminated while RFID tags are being interrogated, and at least one other light is illuminated only when an RFID tag associated with an item meeting a predetermined criterion is illuminated.

27. (Original) The RFID reader of claim 24, wherein the user interface includes more than one light, and the lights are illuminated sequentially as the RFID reader approaches a desired location or material of interest.

28-30. (Canceled)

31. (Currently Amended) An RFID reader comprising:

(a) an RFID interrogation source;

(b) a processor;

(c) a display; and

(d) a user interface that displays an indication in a measurable unit of how far away from an item or location of interest an item currently being interrogated is located, wherein the RFID interrogation source is coupled to the processor and the processor is coupled to the display.

Application No.: «AppNumber»

Case No.: «CaseNumber»

32. (Original) The RFID reader of claim 31, wherein the measurable unit is a number of items.

33. (Original) The RFID reader of claim 31, wherein the RFID reader accounts for missing intermediate items between the item or location of interest and the item currently being interrogated when the indication is displayed.

34. (Canceled) A method of using an RFID reader for interrogating RFID tags associated with items of interest, including the step of:

(a) programming a RFID reader to treat items of interest that are not in a predetermined order as though the items of interest are in the predetermined order.

35. (Canceled) The method of claim 34, wherein the programming step includes programming the RFID reader to treat two items of interest that are transposed relative to the predetermined order as though the two items of interest are in the predetermined order.

36. (Canceled) The method of claim 34, wherein the programming step includes programming the RFID reader to treat an item of interest that is at a location different from its predetermined location by between two to five other items of interest as though it is in the predetermined location in that order.

37. (Canceled) A method of using an RFID reader for interrogating RFID tags associated with items of interest, comprising the steps of:

(a) programming a RFID reader to provide specified information regarding each item of interest in a specified order on a user interface associated with the RFID reader, wherein at least some of the information being selected from the group consisting of a name or title of the item, a serial or call number of the item, and a desired location for the item.

38. (Canceled) A method of using an RFID reader for interrogating RFID tags associated with items of interest, comprising the steps of:

Application No.: «AppNumber»

Case No.: «CaseNumber»

B1
(a) programming a RFID reader to provide specified information regarding a process performed by the RFID reader, wherein at least some of the information being selected from the group consisting of the range of items interrogated, the percentage of items expected to have been interrogated that were not detected, and information indicative of the relative degree of orderliness to the interrogated items.